



TECHNICAL SPECS DATA SHEET

Mikropor Model Name	SDE 2200
---------------------	----------

General Data

Type of Cooling	Air Cooled
Condenser Air Flow (m ³ /h)	5000
Heat Rejection Capacity Max. @45°C (W)	15640
Fan Size (mm)	Ø 400
Number of Condenser Fans	2
Refrigerant Type	R134a
Refrigerant Quantity (kg)	10
Compressor Type	Hermetic / Scroll
Capacity Control (Cycling or Non-Cycling)	Non-Cycling
Expansion System	Thermostatic Expansion Valve
Heat Exchanger Type	Aluminum Plate in Cylindrical Form
Number of Heat Exchangers	2
Suction Line Accumulator Size (lt)	4
Liquid Receiver Size (lt)	10
Drain Type	Membrane Valve (with Solenoid Valve)
Drain Control Type	Electronic Controller
Noise Level (db)	< 70
Filter Allocation and Type	Integrated - GKO2700M X /Y

*

Boundary Conditions

Max Rated Air Flow 35°C Inlet, 7 Barg, 25°C Ambient Temperature (Nm ³ /h)	2200
Relative Humidity (%)	100
Max. Ambient Temperature (°C)	50
Min. Ambient Temperature (°C)	5
Max. Inlet Temperature (°C)	60
Max. Working Pressure (barg)	16

Performance Data

Humidity and Liquid Water Class	ISO8573.1 Class 5 (dew point ≤7°C)
Pressure drop (mbar)	155
At 35°C inlet, Air Temperature at Dryer Outlet (°C)	25 - 30

Electrical Data

Voltage(Volt/Phase/Hz)	400V / 3 / 50 Hz
Total Installed Power (kW) **	4,09
Nominal Operating Ampcity (A) **	10,78
Min. Circuit Ampcity - MCA (A)	16,625
Locked Rotor Amper - LRA (A)	104
Controller Type	DigiPro
Electrical Protection Class according IEC	IP 54
Fuse (A)	20 (will be provided by the user.)

Size / Dimensions / Weight Data

Length (mm)	1163
Width (mm)	778
Height (mm)	1725
Weight (kg)	392

Piping Connections

Connection Size	3"
Drain Connection Size	1"

**Average power consumption (kW, A) is based on 0°C evaporation, 45°C condensation temperature.