



ELESA Original design MRX.p

1 2 3

l_1	d_1	l_2										d_2	h_1	h_2	h_3	h_4	
																	Stroke
42	M 5	10	16	20	-	-	-	-	-	-	-	12	27	6	32	3,5	
42	M 6	10	16	20	25	30	40	-	-	-	-	12	27	6	32	3,5	
63	M 6	10	16	20	25	30	35	40	-	-	-	15	34	8	43	4	
63	M 8	16	20	25	30	35	40	45	50	60	-	15	34	8	43	4	
80	M 10	20	25	30	35	40	50	60	70	-	-	19	42	10	54	4	
80	M 12	20	25	30	35	40	50	60	70	80	-	19	42	10	54	4	
100	M 12	30	50	70	-	-	-	-	-	-	-	25	48	12	65	5	
100	M 14	30	50	-	-	-	-	-	-	-	-	25	48	12	65	5	
100	M 16	30	50	70	-	-	-	-	-	-	-	25	48	12	65	5	

Specification

- Handle
Plastic
Technopolymer (Polyamide PA)
- glass fiber reinforced
- temperature resistant up to 120 °C
- black, RAL 9005, matte ● SW
- Threaded stud
Steel zinc plated, blue passivated
- Releasing button
Plastic, black
- *Plastic characteristics* → Page 1483
- *RoHS compliant*

On request

- with threaded stud Stainless Steel
- different colors

4

Information

Adjustable clamping levers GN 503 are a very cost effective construction variant. In addition these levers are in general rust resistant and electrically insulated.

Furthermore the press button offers an easy disengagement and this also underlines the pleasant design.

Its use is, however, limited to applications where a dismantling of the lever for installation is not required. The threaded insert can after disengagement be screwed in using serration of the insert.

When pulling the handle the serration frees itself and can be re-located into any required position. When releasing the lever the serration re-engages automatically.

How to order

1 2 3 4
GN 503-63-M8-20-SW

1	l_1
2	d_1
3	l_2
4	Color

1.1
1.2
1.3
1.4
2.1
2.2
2.3
2.4

