



L ₀	R	XLL 25%		Max 37,5%		Molle x scatola	
		S ₁	F ₁	S ₂	F ₂		
Lunghezza libera mm	Codice	Rigidità N/mm	Corsa mm	Carico N	Corsa mm	Carico N	
(D) Sede ø mm 20		(d) Spina ø mm 10		Sezione filo 4,0 x 2,4			
25	2S19025	98,0	6,3	613	9,4	919	100
32	2S19032	72,6	8,0	581	12,0	871	100
38	2S19038	56,0	9,5	532	14,3	798	100
44	2S19045	47,5	11,0	523	16,5	784	100
51	2S19050	41,7	12,8	532	19,1	798	100
64	2S19065	32,3	16,0	517	24,0	775	50
76	2S19075	25,1	19,0	477	28,5	715	50
89	2S19090	22,0	22,3	490	33,4	734	50
102	2S19101	19,8	25,5	505	38,3	757	50
115	2S19115	18,1	28,8	520	43,1	781	20
127	2S19126	16,6	31,8	527	47,6	791	20
139	2S19140	15,1	34,8	525	52,1	787	20
152	2S19151	13,2	38,0	502	57,0	752	20
305	2S19303	6,1	76,3	465	114,4	698	10
(D) Sede ø mm 25		(d) Spina ø mm 12,5		Sezione filo 5,3 x 3,1			
25	2S26025	147,0	6,3	919	9,4	1378	100
32	2S26032	118,0	8,0	944	12,0	1416	50
38	2S26038	93,0	9,5	884	14,3	1325	50
44	2S26045	80,8	11,0	889	16,5	1333	50
51	2S26050	68,6	12,8	875	19,1	1312	50
64	2S26065	53,0	16,0	848	24,0	1272	50
76	2S26075	43,2	19,0	821	28,5	1231	20
89	2S26090	38,2	22,3	850	33,4	1275	20
102	2S26101	33,0	25,5	842	38,3	1262	20
115	2S26115	28,0	28,8	805	43,1	1208	20
127	2S26126	25,9	31,8	822	47,6	1233	10
139	2S26140	23,2	34,8	806	52,1	1209	10
152	2S26151	20,8	38,0	790	57,0	1186	10
178	2S26176	17,8	44,5	792	66,8	1188	10
203	2S26202	15,8	50,8	802	76,1	1203	10
305	2S26303	10,2	76,3	778	114,4	1167	5

